



PTTEP

Onsite Supervision Tool



Contents



SSHE Leadership Model	02
Supervisor's Role	04
STOP WORK AUTHORITY	05
Expectation for Frontline Supervisors "PBED"	06
PBED Instructions	
Land Transportation	12
Work at Height	16
Process & Mechanical Isolation	20
Lifting Operation	24
Confined Space Entry	28
System Override	32
Hot Work	36
Electrical Work & Electrical Isolation	40

SSHE Leadership Model





- Trust & Respect
- Recognition
- Feedback
- Credibility



- Competency, Knowledge, Experiences, Awareness
- Adaptability/Flexibility
- Good planning/ implementing/ Controlling
- Hold others accountable (Fair/ Firm/ Consistent)



- Communication
- Collaboration
- Walk the Talk
- Action Orientation
- Follow through with action
- Never turn a blind eye
- Explain the Risk
- Explain the Safety way



- Comply to Legal and PTTEP SSHE MS
- Conform to Site procedures/ guideline/ manual/ instruction, PPE

Supervisor's Roles



- ✓ Visibly demonstrate SSHE leadership.
- ✓ Promote safe behaviors / BBS.
- ✓ Report undesirable events.
- ✓ Ensure that all crews are trained properly and know how to control the risk of assigned task.
- ✓ Ensure that proper risk management are used and communicated, i.e. PTW, JSA, TBT, etc.
- ✓ Ensure that his/her crews properly use and maintain Personal Protective Equipment.
- ✓ Take good care of SSHE at work.
- ✓ Ensure that tools and equipment are kept safe and secure in a good working condition.
- ✓ Ensure compliance with PTTEP SSHE-MS standards and the site operating procedures.
- ✓ Ensure that the handovers between shift or rotation are controlled and documented.
- ✓ Enforce Stop Work Authority.
- ✓ Supervise subcontractors.

STOP WORK AUTHORITY



Supervisors shall lead by example and encourage their subordinate to exercise “STOP WORK”

STOP YOURSELF

- When you are unfit to work.
- When you are in doubt how to do the work steps.
- When your PPE are not properly equipped.

STOP FRIENDS

- When they're exposing line of fire.
- When they're in unsafe action.
- When they're not wearing proper PPE.

4 STOPS

STOP USING

- When tools are damaged, or defected.
- When tools are not certified or inspected.
- When tools are missing safe guard or emergency switch.

STOP DOING

- When there is no Pre-Job Meeting or Toolbox Talk.
- When working condition is changed.
- When new hazard is detected.

Expectation for Frontline Supervisor "PBED"

PLAN

Outline the activity

- Mission
 - Resources
 - Risk Assessment
 - SSHE Procedures
-

BRIEF

Understand the plan

- Expected Target
 - Deployment
 - Own Barrier
-

EXECUTE

Complete the task

- 3P Readiness
 - Supervision
 - Reinforcement
-

DEBRIEF

Close out the job

- Lesson Learned
- Handover
- Fair Treatment

Expectation for Frontline Supervisor “PBED”

PLAN

BRIEF

EXECUTE

DEBRIEF



Outline the activity

Mission:

- Know the activity details, operation requirements, timeline and contingency plan.

Resources:

- Verify the competency of all workers including skill, experience, and required training.
- Lists the required tools and equipment.


Risk Assessment:

- Identify all potential hazards and develop the control and recovery measures.
- Assess the risks and seek an approval from authorized person for performing task.

SSHE Procedures:

- Determine all related SSHE procedures, work operating procedure, and site SSHE Rules.
- Embed all requirements into job pack and work steps.

Expectation for Frontline Supervisor “PBED”



Understand the plan

Expected Target:

- Conduct toolbox talk or pre-job safety meeting with all workers.
- Inform team about the whole mission, activity details, Permit to Work (PTW) scope, and SSHE targets.


Deployment:

- Assign the tasks with individual roles and responsibilities.
- Create two-way communication, ask & listen the team for clear acknowledgement.
- Advise the correct work instruction and safe operating procedures.

Own Barrier:

- Describe the risk assessment with designed control and recovery measures.
- Emphasize Management of Change (MOC) or any deviations from plan.
- Remind team about “STOP WORK AUTHORITY”.

Expectation for Frontline Supervisor “PBED”



Complete the task

3P Readiness (People, Plant, Process):

- Check people; qualified personnel and fitness to work.
- Check plant; readiness and condition of tools and equipment as defined in PTW.
- Check process; control measures in PTW are in place.

Supervision:

- Spend time onsite, be role model and maintain good discipline.
- Coach the team to execute the task in accordance with established SSHE procedures.


Conformance:

- Perform onsite inspection and interview the team for any obstruction.
- Verify and evaluate that all workers' adherence to the documented plan.

Reinforcement:

- Promote BBS observation and highlight safe behaviors.
- Adjust and correct unsafe behaviors and conditions.
- Demonstrate STOP WORK! if any changes occurred. Re-evaluate the risk assessment.

Expectation for Frontline Supervisor “PBED”



Close out the job

Lesson Learned:

- Reconstruct an event to avoid repeat mistakes & clone success.
- Avoid “I already know what went wrong...Here’s simply what we do”.
- Address the lesson learned or any changes in documentation.

Handover:

- Inform responsible parties for job completion and worksite handover.
- Communicate any changes that need to be made.
- Invite all related members for closing meeting.

Fair Treatment:

- Recognize and praise the workers who have good performance.
- Decide an appropriate action for anyone who violate the rules.

PBED Instructions

- LAND TRANSPORTATION
- WORK AT HEIGHT
- PROCESS & MECHANICAL ISOLATION
- LIFTING OPERATION
- CONFINED SPACE ENTRY
- SYSTEM OVERRIDE
- HOT WORK
- ELECTRICAL WORK & ELECTRICAL ISOLATION

- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Also make sure that hazards and control measures are properly defined in each work step.
- ✓ Develop Journey Management Plan (JMP) by considering and including the following:
 - ▶ Route survey
 - ▶ Routine or non-routine (when PTW required)
 - ▶ Route, distance and travelling time
 - ▶ Suitable vehicle selection
 - ▶ Fit to work assessment on nominated driver
 - ▶ Load securement (methods, equipment, etc.)
- ✓ Check and confirm that the driver has a valid driving license and DDC certificate.
- ✓ Check and confirm that driver has had a sufficient rest period to avoid fatigue and has also been verified to have completed a medical check-up.
- ✓ Assign a stand by banksman for heavy vehicles when these vehicles enter a work site.
- ✓ Check and confirm that the vehicle has been inspected as per the PM plan.
- ✓ Check and confirm that all permits & licenses for Dangerous Goods Transportation are in place.
- ✓ Ensure that the vehicle is fully equipped with an IVMS/ GPS system and a DVR camera (if required).



- ✓ Conduct a toolbox talk or pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required and when they feel it is necessary.
- ✓ Ensure that work instructions are efficiently clear enough as per the JMP and safe operating procedures*.
- ✓ Ask the driver to explain the emergency response plan and contact numbers.
- ✓ Confirm the speed limit with driver and encourage that he take rest stops when needed.
- ✓ Emphasize that all drivers fasten their seat belts and the seat belts of all onboard passengers. Remind drivers that the use of a phone while driving is prohibited.

*Relevant document of each asset




- ✓ Conduct alcohol and blood pressure testing prior to trip.
- ✓ Perform random drug testing.
- ✓ Inspect vehicle as per the PTTEP vehicle checklist.
- ✓ Check that all control measures in the JMP have been executed.
- ✓ Monitor each trip status and speed limit via the IVMS/ GPS tracking system.



- ✓ Ask all involved personnel about their previous experience with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If any room for improvement exists, request feedback from the listeners.
- ✓ Recognize and praise the drivers who have performed well.
- ✓ Address any lesson learned or any changes in documentation.
- ✓ Inform responsible parties, such as the fleet controller, upon job completion and delivery status.




- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Make sure that hazards and control measures are properly defined in each work step.
- ✓ Define the access method for working at height e.g. scaffolding, rope access, ladder, etc.
- ✓ Specify/clarify the fall arrest and protection system.
- ✓ Ensure that workers have a valid certificate to work at height.
- ✓ Prepare, if needed, a specific rescue plan, including names of rescue team members, and identification of equipment and facilities.
- ✓ List all tools and equipment taken to the work position/ location at height, to make sure that no tool is left behind.
- ✓ Consider and prepare, if needed, dropped objects prevention tools and their requirements, such as Lanyard, Kick Plate, Safety Net, Tool Bag, etc.



- ✓ Conduct a toolbox talk or pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required and when they feel it is necessary.
- ✓ Ensure that work instructions are efficiently clear enough to work at height and that related safe operating procedures* have been followed.
- ✓ Ask workers to explain how to use the fall protection and arrest system;
 - ▶ Anchorage point
 - ▶ Safe harness practice
- ✓ Encourage that workers complete a 100% tie-off for their harnesses as required.
- ✓ Ask workers to check for loose parts or potential dropped objects.
- ✓ Remind all workers to remain aware of flying objects.


*Relevant document of each asset




- ✓ Confirm that the requirements of the Work Permit have been fulfilled.
- ✓ Inspect the job site to observe whether PPE is being worn as defined in the PTW.
- ✓ Enforce BBS observation and highlight safe behaviors.
- ✓ Ensure that the access method (e.g. scaffolding) is inspected and approved by authorized personnel.
- ✓ Make sure that all workers inspect their fall protection and arrest system before its utilization and work at height.
- ✓ Install barricade and warning signs around any dangerous zones.
- ✓ Count all tools and equipment taken to the work position/location at height, so that no tool is left behind.



- ✓ Ask all involved personnel about their previous experiences with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If any room for improvement exists, request feedback from the listeners.
- ✓ Address the lesson learned or any changes in documentation.



- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Also make sure that hazards and control measures are properly defined in each work step.
- ✓ Embed all SSHE requirements into the job pack and work steps.
- ✓ Ensure that the main & complementary permits to work are accurately completed.
- ✓ Assign the competent personnel for hazard isolation.
- ✓ Prepare a valid P&ID to identify the isolating points.
- ✓ List the required PPEs.
- ✓ Visit worksite before process or mechanical isolation preparation.



- ✓ Conduct a toolbox talk or pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required.
- ✓ Ensure that the work instructions are efficiently clear enough as per the relevant procedures, such as safe operating procedures*.
- ✓ Ask the personnel to confirm the position and method of the equipment isolation as per complementary permit.
- ✓ Remind the emergency call point.

*Relevant document of each asset




- ✓ Confirm that the requirements of the Work Permit have been fulfilled.
- ✓ Inspect the job site to observe whether PPE is being worn as defined in the PTW.
- ✓ Enforce BBS observation and highlight safe behaviors.
- ✓ Confirm that the equipment is fully de-energized and finish up with lock-tag-test-try.
- ✓ Verify the location of the equipment isolation in the working area as per the complementary permit.
- ✓ Install the bund or containment for spill prevention.
- ✓ Ensure that isolation integrity is acceptable to perform.
- ✓ Test all process isolations before breaking any downstream flanges or disconnecting any equipment.



- ✓ Ask all involved personnel about their previous experiences with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If there's any room for improvement, request feedback from the listeners.
- ✓ Recognize and praise the workers who have good SSHE performance.
- ✓ Address the lesson learned or any changes in documentation.
- ✓ Inform responsible parties about the job completion and worksite handover.

- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Also make sure that hazards and control measures are properly defined in each work step.
- ✓ Embed all SSHE requirements into the job pack and work steps.
- ✓ Check that the clearance distance of the overhead power lines is satisfactory.
- ✓ Consider whether installation of hard protection is needed, e.g., scaffolding to prevent live process (flow line, equipment).
- ✓ Classify the Lift category
 - ▶ Routine
 - ▶ Non-routine - Simple
 - ▶ Non-routine - Critical
- ✓ Develop a specific lift plan and approve by authorized person.
- ✓ Prepare the correct SWL and color code of the lifting equipment.
- ✓ Check to make sure that the team has completed a lifting training course and has been certified.



- ✓ Conduct a toolbox talk or a pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required.
- ✓ Ensure that the work instructions are efficiently clear enough as per procedures such as the safe operating procedures*.
- ✓ Confirm that signaling method and line of command are agreed among the lifting task executors and clear.
- ✓ Emphasize any Management of Change (MOC) or any other deviations from the lift plan.
- ✓ Inform all involved personnel to take note of the weather conditions and criteria in order to determine whether to carry out the job, or put it on hold.

*Relevant document of each asset



- ✓ Confirm that the requirements of the Work Permit are in place.
- ✓ Enforce BBS observation and highlight safe behaviors.
- ✓ Utilize the area barricades to prevent unauthorized persons from entering.
- ✓ Check that all lifting equipment is inspected and is in good condition. (Homemade tools are not acceptable.)
- ✓ Check that the rigging method complies with the lift plan and procedures*.
- ✓ Check that a tag line or finger saver tool are used. (No hands are to be on the load.)
- ✓ Ensure that nobody will be under a suspended load.
- ✓ Check that the landing area is clear and in proper condition.

*Relevant document of each asset



- ✓ Ask all involved personnel about their previous experience with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If there's any room for improvement, request feedback from the listeners.
- ✓ Recognize and praise the workers who have good SSHE performance.
- ✓ Address the lesson(s) learned or any changes in documentation.
- ✓ Inform responsible parties about the job completion and worksite handover.



- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Make sure that hazards and control measures are properly defined in each work step.
- ✓ Embed all SSHE requirements into the job pack and work steps.
- ✓ Ensure that the main & complementary permits to work are accurately completed.
- ✓ Ensure that work instructions are efficiently clear enough as per the procedures such as the safe operating procedures*.
- ✓ Check whether the required tools and equipment lists comply with the hazardous area classifications.
- ✓ Check to make sure that the team also has both the confined space entry and fit to work certificates.
- ✓ Check whether the gas tester is currently calibrated and enabled to measure toxic gas.

*Relevant document of each asset



- ✓ Conduct a toolbox talk or pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required.
- ✓ Communicate the required work instructions which are specific for each day-to-day activity.
- ✓ Ask all involved personnel to explain their responsibilities if atmospheric conditions, such as oxygen level, toxic gas level, etc., change.
- ✓ Conduct and give feedback for the emergency drill before commencing the job.
- ✓ Ask all involved parties to explain the emergency and rescue plan.



- ✓ Confirm that the requirements for the work permit are fulfilled.
- ✓ Inspect the job site to observe whether PPE is being worn as defined in the PTW.
- ✓ Enforce BBS observation and highlight safe behaviors.
- ✓ Confirm that gas testing is being carried out as per the work permit and at all levels/ areas in the confined space.
- ✓ Confirm that a qualified standby man is always present when people are in a confined space.
- ✓ Check whether the appropriate rescue equipment is readily available and determine whether this equipment is adequate for that specific confined space configuration.



- ✓ Ask all involved personnel about their experience with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If there's any room for improvement, request feedback from the listeners.
- ✓ Recognize and praise the workers who have good SSHE performance.
- ✓ Address the lessons learned or any changes in documentation.
- ✓ Inform responsible parties about the job completion and worksite handover.



- ✔ Review inhibit/ override document and risk assessment as per the MOC process.
 - ▶ Within 1 day to register it in the logbook
 - ▶ Within 7 days if a work permit was issued
 - ▶ After 7 days of the downgraded situation being issued



- ✓ Conduct a toolbox talk or pre-job safety meeting to ensure hazards and control measures are properly managed with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required.
- ✓ Ensure that the work instructions and emergency response plan are efficiently clear enough as per the procedures such as the safe operating procedures*.
- ✓ Ask an operator to explain his or her responsibility in terms of a system override.
- ✓ Ask an operator to explain an abnormal condition in case of an inhibit/override execution.
- ✓ Handover the inhibit/override information during the shift change.

*Relevant document of each asset



- ✓ Ensure there is an inhibit/override mitigation period before implementing it.
- ✓ Ensure that all mitigation measures defined in the MOC process have been implemented.
- ✓ Ensure inhibit/override applied is displayed on the CCR or written down in the log book.
- ✓ Enforce BBS observation and highlight safe behaviors.




- ✓ Ensure that the system override record is kept and tracked.
- ✓ Ask all involved personnel about their previous experiences with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If there's any room for improvement, request feedback from the listeners.
- ✓ Recognize and praise the workers who have good SSHE performance.
- ✓ Address any lessons learned or any changes in documentation.
- ✓ Inform responsible parties about the job completion, house keeping and worksite handover.

- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Make sure that hazards and control measures are properly defined in each work step.
- ✓ Ensure that operating procedures are in place and reviewed when any non-compliance and SSHE gaps are identified.
- ✓ Embed all mitigations and safety measures into the job pack and work steps.
- ✓ Take Simultaneous Operations (SIMOPs) into consideration when planning for the job.
- ✓ Ensure that main & complementary permits to work are accurately completed.
- ✓ Specify any required PPEs e.g. inherent fire resistance coveralls.
- ✓ Check whether the certificate of tools and equipment comply with the hazardous area classifications.
- ✓ Consider the need for a pressurized habitat.
- ✓ Provide a valid calibration of any gas detectors.
- ✓ Check whether the the competency and training certificate of work for hot work are valid.
- ✓ Prepare and make sure that all required fire fighting equipment is readily available.




- ✓ Conduct a toolbox talk or pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required.
- ✓ Communicate the required work instructions which are specific to the day-to-day activities.
- ✓ Communicate the safe mitigations and controls regarding SIMOPs.
- ✓ Ask an authorized gas tester to explain the testing interval, location, and detection method.

- ✓ Confirm that the requirements for the work permit are fulfilled.
- ✓ Inspect the job site to observe whether PPE is being worn as defined in the PTW.
- ✓ Enforce BBS observation and highlight safe behaviors.
- ✓ Communicate the required work instructions which are specific to each day-to-day activity.
- ✓ Have gas testing conducted by authorized gas tester at appropriate intervals.
- ✓ Confirm whether the positions of the portable fire extinguishers and fire water hose reels are readily accessible near the work location on the upwind side.
- ✓ Ensure that there will be no flanges of any process line located in the pressurized habitat without line isolation or ensure that other appropriate protection has been implemented.
- ✓ Install fire protection blanket(s) to prevent fire sparking.
- ✓ Remove all ignition sources out of hot work area (if possible).
- ✓ Inspect the condition of tools and equipment to be used in hot work activity.




- ✓ Ask all involved personnel about their experience with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If there's any room for improvement, request feedback from the listeners.
- ✓ Recognize and praise the workers who have good SSHE performance.
- ✓ Address any lessons learned or any changes in documentation.
- ✓ Inform responsible parties about the job completion, house keeping and worksite handover.

- ✓ Review the Job Safety Analysis (JSA) to ensure that it is updated and effective. Make sure that hazards and control measures are properly defined in each work step.
- ✓ Embed all SSHE controls and measures into the job pack and work steps.
- ✓ Ensure that main & complementary permits to work are accurately completed.
- ✓ Ensure that work instructions are efficiently clear enough as per the procedures such as the safe operating procedures.
- ✓ Classify the electrical work level e.g. HV, LV.
- ✓ Consider the required PPE needed, such as Arc-Flash PPE for Live Electrical Equipment.
- ✓ Consider all required CPEs (Collective Protection Equipments) and proper tools needed, such as insulated mats, voltage detectors, etc.
- ✓ Provide up-to-date electrical drawings e.g. wiring diagrams, logic diagrams, single line diagrams.
- ✓ If there is a switching operation, the switching program must be approved by senior authorized electrical personnel.
- ✓ Assign only authorized persons for electrical work isolation.
- ✓ Check whether the competency and training certificate of technician is valid, and whether they fit with the electrical work level.
- ✓ If you're in doubt, seek advice from a subject matter expert for a safer operation.



- ✓ Conduct a toolbox talk or pre-job safety meeting with all involved parties.
- ✓ Remind and encourage the team to perform a “STOP WORK AUTHORITY” whenever required.
- ✓ Communicate the required work instructions which are specific to each day-to-day activity.
- ✓ Ask an authorized electrical person to confirm the safety of the isolation method as per complementary permit.
- ✓ Ask a technician to confirm the accuracy of the working location (feeder no., circuit no., compartment no., etc.).
- ✓ Inform all concerned personnel (or make a public announcement) before HV testing, electrical primary injection or electrical de-isolation.



- ✓ Confirm that the requirements for the work permit have been fulfilled.
- ✓ Enforce BBS observation and highlight safe behaviors.
- ✓ Avoid Local Switching - switching operations shall be performed in the ECS (Electrical Control System).
- ✓ Inspect for the readiness and condition of all electrical devices.
- ✓ Identify and Install a boundary barricade to protect against any shocks and arc flashes.
- ✓ Follow Lock out/Tag out (LOTO) and electrical safe work procedure*.
- ✓ Ensure that everyone is wearing all the required PPEs.
- ✓ Confirm the readiness of CPEs as per work planning.
- ✓ Check to ensure that safety status of earthing, bonding, voltage absent verification prior to beginning tasks/ operations.

*Relevant document of each asset



- ✓ Ask all involved personnel about their previous experiences with the SWA.
- ✓ If they've used the SWA, ask them to describe what happened in their situation.
- ✓ If there's any room for improvement, request feedback from the listeners.
- ✓ Recognize and Praise the workers who have good SSHE performance.
- ✓ Address any lessons learned or any changes in documentation.
- ✓ Inform responsible parties about the job completion, house keeping and worksite handover.



PTTEP